

LIGHTING FIXTURE SCHEDULE

CALLOUT	SYMBOL	DESCRIPTION	MODEL	LAMP	LUMENS / LAMP	MOUNTING	INPUT WATTS	VOLTS	NOTES
A		2X4 LAY-IN 4300 LUMEN LED FIXTURE	FLUXWERKS: TR1 24 C 35 F2 M	(1) 38W LED	4300	RECESSED	38	277V 1P 2W	
A1		1X4 LAY-IN ARCHITECTURAL. 2600 LUMENS	FLUXWERKS: TR1 14 A 35K F2 M	(1) 23W LED	2600	RECESSED	23	277V 1P 2W	
A1E		1X4 LAY-IN ARCHITECTURAL. 2600 LUMENS WITH 90-MINUTES BATTERY BACKUP	FLUXWERKS: TR1 14 A 35K F2 M B	(1) 23W LED	2600	RECESSED	23	277V 1P 2W	
AE		2X4 LAY-IN 4300 LUMEN LED FIXTURE WITH 90-MINUTE BATTERY BACKUP	FLUXWERKS: TR1 24 C 35 F2 M B	(1) 38W LED	4300	RECESSED	38	277V 1P 2W	
B		6" LED DOWNLIGHT 1500 LUMENS	LITHONIA: LDN6 35/15 L06 AR LSS MVOLT E210 TRW	(1) 23W LED	1606	RECESSED	23	277V 1P 2W	
BB		STEP LIGHTS IN PERIMETER CONCRETE WALL	SISTEMALUX: C.8022N // 4551 0024 080 120 LTE	(1) 10W LED	310	WALL	10	120V 1P 2W	PROVIDE REMOTE POWER SUPPLY AS REQUIRED
BE		6" LED DOWNLIGHT 1500 LUMENS WITH 90-MINUTES BATTERY BACKUP	LITHONIA: LDN6 35/15 L06 AR LSS MVOLT E210 TRW EL	(1) 23W LED	1606	RECESSED	23	277V 1P 2W	
BW		LED DOWNLIGHT SUITABLE FOR WET ENVIRONMENTS	LITHONIA: LDN6 35/15 L06 AR LSS MVOLTE210 TRW WL	(1) 23W LED	1606	RECESSED	23	277V 1P 2W	
C		4-FOOT LENSED LED STRIP 3800 LUMENS	LITHONIA: ZL1D L48 3000LM FST MVOLT 35K 80CRI WH / ZACVH	(1) 33W LED	3830	SURFACE / SUSPENDED	33	277V 1P 2W	
CE		4-FOOT LENSED LED STRIP 3800 LUMENS WITH 90-MINUTE BATTERY BACKUP	LITHONIA: ZL1D L48 3000LM FST MVOLT 35K 80CRI WH / ZACVH E7W	(1) 33W LED	3830	SURFACE / SUSPENDED	33	277V 1P 2W	
D		8" LED CYLINDER DOWNLIGHT. STEM MOUNTED 3000 LUMENS	LITHONIA: LDN6CYL 35/30 L06 AR LSS MVOLT E210 PM-CYS-XX	(1) 35W LED	3034	PENDANT	35	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
DE		8" LED CYLINDER DOWNLIGHT. STEM MOUNTED 3000 LUMENS WITH BATTERY BACKUP VIA INVERTER	LITHONIA: LDN6CYL 35/30 L06 AR LSS MVOLT E210 PM-CYS-XX	(1) 35W LED	3034	PENDANT	35	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F6		4" LINEAR SLOT 6 FOOT LONG DIRECT/INDIRECT PATTERN WITH TOP/BOTTOM GLOW LENS, AIRCRAFT CABLE SUSPENSION DUAL SWITCH/DIMMING CIRCUITS. CROSS HATCHED SECTIONS INDICATE 24" EM MODULE.	FINELITE: HP-4 ID 6' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 66W LED	6920	PENDANT	66	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F7		SAME AS F6 WITH 7' LONG PATTERN.	FINELITE: HP-4 ID 7' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 77W LED	8085	PENDANT	77	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F8		SAME AS F6 WITH 8' LONG PATTERN.	FINELITE: HP-4 ID 8' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 88W LED	9240	PENDANT	88	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F12		SAME AS F6 WITH 12' LONG PATTERN.	FINELITE: HP-4 ID 12' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 132W LED	13860	PENDANT	132	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F13.5		SAME AS F6 WITH 13.5' LONG PATTERN.	FINELITE: HP-4 ID 13.5' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 149W LED	15592	PENDANT	149	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F15		SAME AS F6 WITH 15' LONG PATTERN.	FINELITE: HP-4 ID 15' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 165W LED	17325	PENDANT	165	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F17		SAME AS F6 WITH 17' LONG PATTERN.	FINELITE: HP-4 ID 17' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 187W LED	19635	PENDANT	187	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F17.75		SAME AS F6 WITH 17.75' LONG PATTERN.	FINELITE: HP-4 ID 17.75' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 187W LED	19635	PENDANT	187	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F18.5		SAME AS F6 WITH 18.5' LONG PATTERN.	FINELITE: HP-4 ID 17.5' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 204W LED	21367	PENDANT	204	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
F19.75		SAME AS F6 WITH 19.75' LONG PATTERN.	FINELITE: HP-4 ID 19.75' S H 835 WSOTG BG 277V FA DC C4 (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 217W LED	22811	PENDANT	217	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
FS5		4" LINEAR SLOT 5 FOOT LONG PATTERN SURFACE DIRECT WITH BOTTOM GLOW LENS. CROSS HATCHED SECTIONS INDICATE 24" EM MODULE.	FINELITE: HP 4 SM 5' H 835 BG 277V C4 SC (INCLUDE BSL722 FOR EMERGENCY AS HATCHED ON PLAN)	(1) 28W LED	2882	SURFACE	28	277V 1P 2W	
G4		4" LINEAR SLOT 4 FT LONG PATTERN SURFACE MOUNTED WALL DIRECT/INDIRECT WITH TOP AND BOTTOM GLOW LENS	FINELITE: HP-4 WM ID 4' S B 835 TG BG 277 MB SC	(1) 33W LED	3618	WALL / SURFACE	33	277V 1P 2W	PROVIDE LENGTH TO MATCH COVE, TELESCOPING SECTIONS AND APPURTENANCES FOR A COMPLETE AND OPERATIONAL SYSTEM

LIGHTING FIXTURE SCHEDULE (CONT.)

CALLOUT	SYMBOL	DESCRIPTION	MODEL	LAMP	LUMENS / LAMP	MOUNTING	INPUT WATTS	VOLTS	NOTES
G6		SAME AS G4 WITH 6 FT LONG PATTERN	FINELITE: HP-4 WM ID 6' S B 835 TG BG 277 MB SC	(1) 50W LED	3613	WALL / SURFACE	50	277V 1P 2W	PROVIDE LENGTH TO MATCH COVE, TELESCOPING SECTIONS AND APPURTENANCES FOR A COMPLETE AND OPERATIONAL SYSTEM
G8		SAME AS G6 WITH 8 FOOT LONG PATTERN	FINELITE: HP-4 WM ID 8' S B 835 TG BG 277 MB SC	(1) 66W LED	4818	WALL / SURFACE	66	277V 1P 2W	PROVIDE LENGTH TO MATCH COVE, TELESCOPING SECTIONS AND APPURTENANCES FOR A COMPLETE AND OPERATIONAL SYSTEM
G10		SAME AS G6 WITH 10 FOOT LONG PATTERN	FINELITE: HP-4 WM ID 10' S B 835 TG BG 277 MB SC	(1) 83W LED	6022	WALL / SURFACE	83	277V 1P 2W	PROVIDE LENGTH TO MATCH COVE, TELESCOPING SECTIONS AND APPURTENANCES FOR A COMPLETE AND OPERATIONAL SYSTEM
G13		SAME AS G6 WITH 13 FOOT LONG PATTERN	FINELITE: HP-4 WM ID 13' S B 835 TG BG 277 MB SC	(1) 108W LED	7830	WALL / SURFACE	108	277V 1P 2W	PROVIDE LENGTH TO MATCH COVE, TELESCOPING SECTIONS AND APPURTENANCES FOR A COMPLETE AND OPERATIONAL SYSTEM
H10		TRACK SYSTEM FOR GUN RANGE LIGHTING AND 10 TRACK HEADS	JUNO: TRACK: T4BL T8BL T12BL // TOLFM11BL / TCLO AMP BL HEAD: T1038 E26 BL UL MAX WATT LABEL 25W + PAR38 FL BLACK	(10) 25W LED	0	COVE	250	277V 1P 2W	PROVIDE TRACK SECTIONS CONNECTORS AND APPURTENANCES NEEDED FOR A COMPLETE AND OPERATIONAL SYSTEM.
H12		TRACK SYSTEM FOR GUN RANGE LIGHTING AND 12 TRACK HEADS	JUNO: TRACK: T4BL T8BL T12BL // TOLFM11BL / TCLO AMP BL HEAD: T1038 E26 BL UL MAX WATT LABEL 25W + PAR38 FL BLACK	(12) 25W LED	0	COVE	300	277V 1P 2W	PROVIDE TRACK SECTIONS CONNECTORS AND APPURTENANCES NEEDED FOR A COMPLETE AND OPERATIONAL SYSTEM.
H20		TRACK SYSTEM FOR GUN RANGE LIGHTING AND 20 TRACK HEADS	JUNO: TRACK: T4BL T8BL T12BL // TOLFM11BL / TCLO AMP BL HEAD: T1038 E26 BL UL MAX WATT LABEL 25W + PAR38 FL BLACK	(20) 25W LED	0	COVE	500	277V 1P 2W	PROVIDE TRACK SECTIONS CONNECTORS AND APPURTENANCES NEEDED FOR A COMPLETE AND OPERATIONAL SYSTEM.
K		17"x18"-3" CUSTOM "CROSS PATTERN" SUSPENDED DIRECT /INDIRECT WITH TOP AND BOTTOM GLOW LENS	FINELITE: HP4 ID CUSTOM CROSS PATTERN (17"x8"-3") S H 835 WSOTG BG 277V FA DC C4	(1) 275W LED	28750	SUSPENDED	275	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
L		6" RECESSED DOWNLIGHT "DOUBLE WALL WASHER"	EDISON PRICE: AP CLW6 L30 35K 277 DWW ECOL	(1) 40W LED	2580	RECESSED	40	277V 1P 2W	
LE		6" RECESSED DOWNLIGHT "DOUBLE WALL WASHER" WITH 90-MINUTE BATTERY BACKUP	EDISON PRICE: AP CLW6 L30 35K 277 DWW ECOL RM	(1) 40W LED	2580	RECESSED	40	277V 1P 2W	
M		22" DIAMETER HIGH BAY WITH FROSTED REFRACTOR	BEGHELLI: BS830LED 125 WT30 22ACW PK XX" 120-277 AL	(1) 131W LED	15790	SUSPENDED	131	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
P		MICRO LINEAR RECESSED DOWNLIGHT	IGUZZINI: I.P474-120-02-LTE	(1) 13W LED	618	CEILING	13	277V 1P 2W	
Q		SMALL DECORATIVE PENDANT	BRUCK: 137 206 XTM19 35K 83 DA40 UNV ELV MC MP FINISH	(1) 12W LED	935	SUSPENDED	12	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
R		6" DECORATIVE RECESSED DOWNLIGHT	ALPHABET: 621 XTM19 20LM 35K 83 DA60 277 DIM10 NC 6ZLR6	(1) 25W LED	1700	RECESSED	25	277V 1P 2W	
RE		6" DECORATIVE RECESSED DOWNLIGHT WITH 90-MINUTE BATTERY BACKUP	ALPHABET: 621 XTM19 20LM 35K 83 DA60 277 DIM10 NC 6ZLR6 EM7	(1) 25W LED	1700	RECESSED	25	277V 1P 2W	
S		48"x18" DECORATIVE TRILAM FABRIC PENDANT	BARBICAN: 16 77 48D 18H LF TBD SM HTO RAL LED108W 277V 3500K 80CRI DB(0-10V)	(1) 144W LED	0	SUSPENDED	144	277V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
SA		POLE-MOUNTED LED FIXTURE WITH FORWARD THROW DISTRIBUTION. AND HOUSE SHIELD	LITHONIA: DSX1 LED P6 40K TFM MVOLT HS SPA DDBXD SSS 254G DMA19AS DDBXD	(1) 163W LED	19000	POLE	163	277V 1P 2W	PROVIDE MATCHING 20' SQUARE POLE
SB		POLE-MOUNTED LED FIXTURE WITH TYPE V DISTRIBUTION	LITHONIA: DSX1 LED P6 40K T5W MVOLT HS SPA DDBXD SSS 254G DMA19AS DDBXD	(1) 163W LED	19000	POLE	163	277V 1P 2W	PROVIDE MATCHING 20' SQUARE POLE
SP		ABOVE GRDE "POWER PIPE" MOUNTED SPOT WITH INTEGRAL POWER SUPPLY	BK LIGHTING: DE LED X66 SP BZW 9 A PPII S18 D24INC B MT SF	(1) 24W LED	1923	ABOVE GRADE	24	277V 1P 2W	
U4		4' SURFACE WALL BRACKET	LITHONIA: WL4 40L EZ1 LP835	(1) 40W LED	4124	WALL	40	120V 1P 2W	MOUNTING HEIGHT AND FINISH TO BE APPROVED BY ARCHITECT
UC		UNDER COUNTER WITH LINKABLE MODULES	FEELUX: TUN(7) (11) (15) 40K ST STD S HW NON 120	(1) 15W LED	1500	SURFACE TO MILLWORK	15	120V 1P 2W	VERIFY FINAL LENGTH IN THE FIELD PRIOR TO PROCUREMENT
W		DECORATIVE EXTERIOR SCOFFER WITH TYPE 4 DISTRIBUTION	LITHONIA: WST LED P2 40K VW MVOLT DDBXD	(1) 25W LED	3515	WALL	25	277V 1P 2W	15'-0" AFG
WE		SMALL DECORATIVE EXTERIOR SCOFFER WITH PHOTOCELL CONTROL	GARDCO: 111L 16L 550 WW-G2 4 UNV PCB XX	(1) 28W LED	2600	WALL	28	277V 1P 2W	6" ABOVE DOOR. VERIFY FINISH WITH ARCHITECT PRIOR TO PROCUREMENT
X1		SINGLE FACE EDGE LIT EXIT SIGN RED LETTER AND SELF DIAGNOSIS	LITHONIA: EDGR 1 R EL SD	(1) 5W LED	0	WALL/CEILING	5	277V 1P 2W	
Y1		GROUND MOUNTED ASYMETRIC LINEAR WALL WASHER ACCENT	LUMENPULSE: LOG HO 120 48 30K WRRF SAM BK DIM	(1) 61W LED	3588	GROUND	61	120V 1P 2W	MOUNT 5 FT AWAY FROM WALL AT 10'-0" O.C.
Y2		ROOF-MOUNTED ASYMETRIC LINEAR WALL WASHER ACCENT	LUMENPULSE: LOG RO 120 48 30K WRRF SAM BK DIM	(1) 34W LED	1757	ROOF	34	120V 1P 2W	U.N.O. MOUNT 5 FT AWAY FROM WALL AT 10'-0" O.C.

PRELIMINARY NOT FOR CONSTRUCTION

THIS DOCUMENT IS RELEASED FOR THE PURPOSE OF INTERIM REVIEW UNDER THE AUTHORITY OF ROBERTO TORRES, P.E. LICENSE # 83419. IT IS NOT TO BE USED FOR CONSTRUCTION, OR PERMIT PURPOSES.

Revision Schedule

Rev. #	Revision Description	Revision Date



Torres Engineering Services, Inc. Texas Firm Number F-10147 8237 DeSoto Blvd. Ft. Worth, TX 76131 Tel: 817-506-0848 Fax: 817-345-3552 Project # 1800

OWT ARCHITECTS

509 PECAN STREET SUITE 100 FORT WORTH, TX 76102 817.993.9844

www.owtarchitects.com

TEXAS GUN EXPERIENCE

GRAPEVINE, TEXAS

2016-028-00 DECEMBER 1 2017

LIGHTING FIXTURE SCHEDULE

E5.2